



## RT3 HTX SPECIFICATIONS

7'0"  
Steel / Poly / Stainless  
HTX

7'6"  
Steel / Poly / Stainless  
HTX

### MOLDBOARD

Moldboard Width (Straight)	84" (213 cm)	90" (229 cm)
Plowing Width @ 30 Deg. Angle	73" (185 cm)	78" (198 cm)
Moldboard Material	14-ga mild steel / 1/4" poly / 14-ga stainless steel	14-ga mild steel / 1/4" poly / 14-ga stainless steel
Moldboard Height	26" (66 cm)	26" (66 cm)
Cutting Edge (1080 Steel)	1/4" x 6" (.6 cm x 15 cm)	3/8" x 6" (1 cm x 15 cm)
Cutting Edge Angle	70°	70°
Reinforcement Ribs	4 Vertical, 2 Diagonal	6 Vertical, 2 Diagonal
Pivot Pin Bushings (O.D. / I.D.)	1-1/2"(38mm) / 11/16"(17.5mm)	1-1/2"(38mm) / 11/16"(17.5mm)
Snowfoil	Optional	Optional

### PUSH FRAME ATTACHMENT BAR

Cross Bracing	1-1/2"(38mm) x 3/16"(4.8mm) Plate	1-1/2"(38mm) x 3/16"(4.8mm) Plate
Moldboard Attachment Pins	5/8"(15.9mm) GR5, QTY 2	5/8"(15.9mm) GR5, QTY 2
Pivot Pin Diameter	5/8"(15.9mm) GR5	5/8"(15.9mm) GR5

### PUSH FRAME

Super Structure	1-11/16" x 2" x 3/16"	1-11/16" x 2" x 3/16"
Cross Bracing	1-9/16" x 3/16" Plate	1-9/16" x 3/16" Plate
Angle Pivot Pin Diameter	5/8"(15.9mm) GR5	5/8"(15.9mm) GR5
Pivot Pin Bushing (O.D. / I.D.)	1-1/2"(38mm) / 11/16"(17.5mm)	1-1/2"(38mm) / 11/16"(17.5mm)

### TRIP MECHANISM

Trip Method	Full Moldboard	Full Moldboard
Trip Springs	2	2
Trip Spring Type	0.375" Hooked Extension Spring	0.375" Hooked Extension Spring
Trip Spring Adjustment	Spade Bolt	Spade Bolt

### LIGHTING

Bulbs	SL3 L.E.D. with Ice Shield Technology
Lens Material	Fully Sealed L.E.D. Lighting
Housing Material	Polycarbonate
Dimensions	Xenoy
Mounting	11-1/2"(292mm) Wide X 4 1/3"(110mm) High X 6"(152mm) Deep
High beam output	Fully adjustable 5 bolt retaining clamp
Low beam output	850 effective lumens
	650 effective lumens
	100% DOT, FMVSS, SAE and ECE compliant

### CONTROLS

SmartTouch 2™ Hand Held Control (standard):	3 Soft Touch Illuminated buttons - Automatic Float Fully Independent Function Control
Joystick (optional):	4 position Joystick with Detented Float Position Fully Independent Function Control

### HYDRAULIC SYSTEM PERFORMANCE

Angling	3-1/2 Seconds at Full Pressure
Lift	2 Seconds at Full Pressure
Lower	Pre-set Flow Control

### POWER UNIT

Construction	Heavy Duty, Cast Iron Pump Housing
Mounting	Plow Mounted with Enclosure Cover
Reservoir Capacity	2 Quart
Type	Fixed Displacement Gear Pump, 1/8" Wide Gear Face (.065 cu.in/rev)
Flow Rate	.85 GPM (3.2 LITER/MIN) @ 1500 PSI
Motor	12 VDC High Torque Motor
Amp Draw	125 Amps, 12 VDC, @ 1500 PSI
Relief Setting	2000 PSI Full Bypass Relief
Filtration	100 Mesh Screen on Inlet and Exhaust Tubes



## RT3 HTX SPECIFICATIONS

### CYLINDERS

#### Angling Cylinders

Quantity

Stroke

Rod Diameter

Seal

#### Lift Cylinders

Quantity

Type

Stroke

Rod Diameter

Piston Diameter

Seal

7'0"  
Steel / **Poly** / Stainless  
HTX

7'6"  
Steel / **Poly** / Stainless  
HTX

2

6-1/2"(165mm)

1-1/2"(38mm)

Polyurethane and Buna-N Double Lip Seals

2

6-1/2"(165mm)

1-1/2"(38mm)

Polyurethane and Buna-N Double Lip Seals

1

Direct Acting, Pull Type

10"(254mm)

1.125"(28.6mm)

1.750"(44.5mm)

Polyurethane and Buna-N Double Lip Seals

1

Direct Acting, Pull Type

10"(254mm)

1.125"(28.6mm)

1.750"(44.5mm)

Polyurethane and Buna-N Double Lip Seals

### VALVE MANIFOLD

Type

Material

Valves

Remote Mounted, Cartridge Valve Manifold  
Anodized 6061 Marine Grade Aluminum  
2 Solenoid-Operated, 2-Way, Piloted Poppet Control Valves  
1 Solenoid-Operated, 4-Way, 3 Position Spool Control Valve  
1 Cross-over Relief Valve (3800 PSI Setting)  
3 100 Mesh Filter Screens

### QUICK HITCH SYSTEM

Undercarriage System

Hitch System

RT3  
SmartHitch 2™

RT3  
SmartHitch 2™

### MISCELLANEOUS

Blade Adjustable Plow Shoe

Optional Cast Iron Wear Pad with 1"(25.4mm) Steel Rod.

Optional Cast Iron Wear Pad with 1"(25.4mm) Steel Rod.

### PLOW WEIGHT\*

393 lb (178kg) / **367 lb (166kg)** / 393 lb (178kg)

440 lb (200 kg) / **416 lb (188 kg)** / 440 lb (200 kg)

### WARRANTY

Limited 2 year  
Parts and Labor

Limited 2 year  
Parts and Labor

\* Plow weight does not include mount weight. Vehicle mount weight range: 45-75 lb.

BOSS Products, a division of The Toro Company, reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used herein.

5/16/2017 GP